



Single Channel Linear DC Power Supplies

Over voltage protection

Over current protection

Over temperature protection

Short circuit protection

High resolution display

Low ripple/noise

Display 3.7 inch TFT LCD



Technical Specifications

Model		Nvis 1305P	Nvis 1603P
Output		0-30V/0-5A	0-60V/0-3A
Load Regulation	Voltage	≤0.01% ±3mV	
	Current	≤0.01% ±3mV	
Ripple/Noise (20Hz-20MHz)	Voltage	≤1mVrms / ≤4mVp-p	
	Current	4mA _{rms}	
Setting Resolution	Voltage	1mV	
	Current	1mA	
Set Point Accuracy (25°C ± 5°C)	Voltage	≤0.03% ±10mV	
	Current	≤0.01% ±5mV	
Response Time		100 μs	
Interface		RS232	
General information :			
Power supply		: 230V±10%, 50Hz	
Operating temperature		: 0-40°C	
Dimension (mm)		: W 117 X H 194 X D 295	
Weight		: 5.6 Kg (approximately)	
Included accessory		: Mains cord	

Nvis Technologies Pvt. Ltd.

141-A, Electronic Complex, Pardesipura, Indore-452010, India.

© +91-731-4211500, ✉ info@nvisotech.com, 🌐 www.NvisTech.com